Examining dependencies among different time scales in episodic memory - An
experience sampling study

Hyungwook Yim

School of Psychological Sciences, The University of Melbourne, Australia
Division of Psychology, School of Medicine, University of Tasmania, Australia

Paul M. Garrett, Megan Baker

School of Psychology, The University of Newcastle, Australia

Vishnu Sreekumar

Surgical Neurology Branch, National Institute of Neurological Disorders and
Stroke, National Institutes of Health, USA

Simon J. Dennis

School of Psychological Sciences, The University of Melbourne, Australia

Author Note

This research was supported under Australian Research Council's Discovery Projects funding scheme to SJD (DP150100272). Note that SJD is the CEO of a startup called Unforgettable Technologies Pty Ltd that specializes in providing privacy preserving experience sampling collection and analysis services. Part of the study was presented at the 40th Annual Conference of the Cognitive Science Society. Correspondence concerning this article should be addressed to Simon J. Dennis (School of Psychological Sciences, The University of Melbourne, Melbourne, VIC, 3010, Australia. E-mail: simon.dennis@gmail.com. Telephone: +61-3-8344-6377).

Abstract

We re-examined whether memories of different time scales such as week, day of week, and hour of day are used independently during memory retrieval as has been previously argued (*i.e.*, independence of scales). To overcome the limitations of previous studies, we used experience sampling technology to obtain test stimuli that have higher ecological validity and used pointwise mutual information to directly measure the degree of dependency in a formal way. Participants wore a smartphone around their neck for two weeks, which was equipped with an app that automatically collected time, images, GPS, audio and accelerometry. After a one-week retention interval, participants were presented with an image that was captured during their data collection phase, and were tested on their memory of when the event happened (*i.e.*, week, day of week, and hour). We find that, in contrast to previous arguments, memories of different time scales were not retrieved independently. Moreover, through rendering recurrence plots of the images that the participants collected, we provide evidence the dependency may have originated from the repetitive events that the participants encountered in their daily life.

Keywords: time scale dependency; experience sampling; episodic memory; autobiographical memory

Examining dependencies among different time scales in episodic memory - An experience sampling study

When trying to remember when a past event happened, people are able to retrieve time information from different scales such as the year, month, day of month, and hour of the event (*e.g.*, Friedman & Wilkins, 1985). How are people able to remember different time scales of an event and how are memories of different time scales represented? Friedman and Wilkins (1985) examined a couple of hypotheses. One reasonable hypothesis was that time information is estimated by the strength of the memory that decays over time, and different scales are associated to a single point on this memory-strength continuum (see Figure 1A). Therefore, in the strength hypothesis (*e.g.*, Hinrichs, 1970), different time scales naturally become interdependent. Moreover, since coarser time scales have a wider coverage on the continuum, the strength-based view predicts that if a finer time scale (*e.g.*, hour) is correctly remembered, a coarser time scale (*e.g.*, year) will likely be remembered. Consequently, a directional dependence exists in remembering time scales, where the probability of correctly remembering a coarser time scale is affected by the probability of correctly remembering a finer time scale.

To illustrate the dependency we present a simulation using a formal version of the strength hypothesis as follows (see Figure 2). Suppose one is trying to remember an event during a two-week vacation, and the true event happened on Week1, Tuesday 10am. Following the strength hypothesis, there will be a specific strength attached to this time point, and we will assume that there will be some noise, which follows a normal distribution centered on the target time point (see Figure 2A). Then the probability correct of the week scale (*i.e.*, week1) can be

estimated by calculating the area under the curve where the memory strength is smaller than the border of week-1 and week-2 (shaded in green in Figure 2A). Probability correct for the day and hour scale can also be calculated in the same fashion. However, for the day scale there will be two Tuesdays one for each week (shaded in yellow), and for the hour scale there will be ten points for 10am, one for each weekday (shaded in orange). Following this method, Figure 2B shows the probability correct for the three scales, where we took the average of all possible target time points in the study. Regardless of the degree of noise in the signal (i.e., SD; standard deviation of the normal distribution), the model always predicts that the coarser time scale (i.e., week scale) will be more accurately retrieved than the finer time scale (i.e., hour scale).

On the other hand, Friedman and Wilkins (1985) provided evidence that time scales are not linked to each other as the strength hypothesis proposes, but rather, retrieval cues for each time scale exist (reconstructive hypothesis; see Figure 1B). In their study, participants were presented with popular news events (*e.g.*, John F. Kennedy's assassination), and were asked about when the events happened on different time scales (*e.g.*, year, month, day of month, day of week, and hour). Results showed that in some cases remembering a finer time scale was more accurate than remembering a coarser time scale (*i.e.*, scale effects). Scale effects support the idea that people could use different cues to retrieve different time scales of the event rather than only relying on the overall memory strength of an event (Friedman, 1993). Similar results have been reported using different materials. For example, Friedman (1987) asked participants about when a local earthquake happened, Huttenlocher, Hedges, and Prohaska (1992) asked participants, who previously responded to a phone survey, the day of week and time of the phone survey, and Larsen and Thompson (1995) asked when events in participants' diaries happened. Although

Friedman and Wilkins (1985) originally provided evidence for the scale effects to support the reconstructive hypothesis, the results are often interpreted as evidence also for independent time scales, which predicts that correctly remembering one time scale is unaffected by remembering another time scale (*e.g.*, Friedman, 1993; Neath & Surprenant, 2002).

However, it is hard to conclude that time scales are independent from these results for two main reasons. First, it is possible that the materials used in previous studies are not fully representative of our day to day life events. Historical and media events (*e.g.*, John F. Kennedy's assassination) may have less self-relevance than our day to day events, or may be more salient than the typical events that occur on a daily basis (*e.g.*, local earthquake). Diary studies have the issue of selection bias, where more salient events are more likely to be recorded by the participants than regular events (Sreekumar, 2015). An alternative way to examine the nature of time scale representation with better ecological validity is using passive experience sampling techniques. Experience sampling has the advantage of collecting each participant's day to day events automatically without selection-bias, and by utilizing modern smartphones, various modalities may be easily recorded such as time, images, sounds, GPS, and accelerometry. Previous memory studies using experience sampling techniques have been successful in showing interesting findings about human memory in real life ranging from the kinds of cues people use to remember when an event happened, to how time and space are represented in the brain (*e.g.*, Chow & Rissman, 2017; Dennis, Yim, Sreekumar, Evans, Garrett, & Sederberg 2017; Nielson, Smith, Sreekumar, Dennis, & Sederberg, 2015; Sreekumar, Dennis, Doxas, Zhuang, & Belkin, 2014; Sreekumar, Nielson, Smith, Dennis, & Sederberg, 2018).

Second, previous studies have not used a formal measure of dependency. Although the

results from these studies (*e.g.*, scale effects) serve as a counter-example against the strength hypothesis, they are not sufficient to support the claim that time scales are independent. A proper measure of dependency, such as pointwise mutual information (PMI) between time scales, is required.

Therefore, in the current study we used experience sampling techniques to examine whether memories of different time scales are independently used and represented (*i.e.*, independence of scales), and whether scale effects are present in everyday life. We also utilize a formal measure of dependency (*i.e.*, PMI) to examine the magnitude of dependencies among different time scales. In the experiment, participants collected their day to day life events for two weeks using a smartphone which automatically collected various kinds of information including images of their surroundings and the time of when these images were taken. Then, participants were presented with images that they had collected and were asked what week, day of week, and hour of day the event depicted by the image happened. Additionally, we asked how confident the participants were in making each judgment.

Experiment

Methods

Participants. Nineteen adults participated in the study (ten females, $M = 26.47$ yrs, $SD = 6.30$ yrs). Participants were recruited from flyers posted around campus and were paid AU\$100 for their time and effort. The research was approved by The University of Newcastle Human Research Ethics Committee.

Materials. The images used in each participant's experiment were selected from each participant's data, which was accumulated during the data collection period. Images were

processed first by filtering out blurry images that had entropy values below 17.0 or variation of the Laplacian (Pech-Pacheco, Cristobal, Chamorro-Martinez, & Fernandez-Valdivia, 2000) below 7.0. Then one image for each one-hour slot was selected based on how different the image was compared to other images in other time slots. The difference between images was calculated by the Euclidean distance of each image's *gist* representation (Oliva & Torralba, 2001), where the image with the highest minimum-distance was selected for a given hour slot. For example, assume there are three images (*e.g.*, A, B, C) in a given hour slot. We calculate the distance (*i.e.*, Euclidean distance of *gist* representations) between A and all other images outside of the given hour slot (*e.g.*, X, Y, Z) and take the minimum value among them as a distance measure for image A (*i.e.*, minimum-distance). We repeat this process for all images in the given time slot (*i.e.*, images B and C). Then we pick the image that has the highest minimum-distance measure among the three in order to choose the image that is the most distinct from images of other hour slots. Since different number of images were collected by each participant, the number of images used at test were different across participants ($M = 67.58$, $SD = 27.17$, $range = 22 - 122$).

Procedure. There was a two-week data collection phase followed by a one-hour test phase, which was separated by approximately seven days. The data collection phase always started on a Monday and ended on the Friday of the following week. During the data collection phase, participants were told to wear a smartphone around their neck during the weekdays when they were awake, as much as possible (see Figure 3A). The phone was equipped with the 'Unforgettable' app. (Dennis, Yim, Sreekumar, Garrett, & Stone, 2018; Unforgettable Technologies, 2017), which collected image, time, audio (*i.e.*, obfuscated information using mel-frequency cepstrum coefficients), GPS, accelerometer and orientation information every five

minutes or when a movement was sensed by the phone (see Figure 3B for the layout of the app.). Participants had full control over the app. and could turn off the app. anytime they needed privacy. The stored data was automatically sent to a remote server when the phone detected WiFi and was charged above 90%, which usually happened once per day when users charge the phone overnight.

Seven days after the data collection phase (*i.e.*, on the third Friday), participants were asked to login to an online webpage for the test phase. Participants were randomly presented with a selection of their images collected during the data collection phase. The images were presented one at a time on the left side of the screen with related questions on the right side (see Figure 4). Participants were asked in which week, day, and hour the event captured in the image happen, and were asked to make a confidence rating on a five point scale for each response. The valence/arousal of the event was also elicited using a five-point scale. The number of test trials differed based on the number of images that were collected by each participant during the data collection phase (see Materials). The valence/arousal data is irrelevant to the current investigation and will be reported elsewhere.

In addition to the current task, a study-test memory task using the collected images was administered on the third Monday (*i.e.*, approximately four days before the current test phase). The task was irrelevant to the current investigation in that participants did not make judgments or receive feedback about the time information of the images. The results of this task will be reported elsewhere.

Results and Discussion

The pooled group data was analyzed with bootstrapping methods (Efron & Tibshirani,

1997). The pooled group data was re-sampled by subject 1,000,000 times with replacement.

We first examined the accuracy for each time scale using a one-sample t-test against chance level. Although chance level for P (*hour*) would be $1/24$, most participants did not collect data for 24 hours. The average of the maximum hour that participants collected data per day was 13.42 hours ($SD = 3.05$, $range = 8 - 24$), and we used $1/13$ as the chance level for P (*hour*). Results show that performance for all time scales were above chance (see Table 1), which indicates that participants were capable of recalling when an event happened in different time scales with reasonable precision. Participants also showed above chance performance in correctly remembering the exact week, day, and hour information of an event, P (*week*, *day*, *hour*) = .065 ($SD = .011$), chance-level = .008 ($= 1/2 \times 1/5 \times 1/13$), $p < .001$.

We also used error scores to examine the degree of accuracy following Friedman and Wilkins (1985). Error scores were calculated by taking the shortest distance between the participant's response and the actual time, and then dividing the distance by the deviation expected by chance (DEC). DEC is the deviation that could be expected by random guessing, where it was .5 ($= \{0 + 1\}/2$) for week, 1.2 ($= \{0 + 2 \cdot (1 + 2)\}/5$) for day, and 3.23 ($= \{0 + 2 \cdot (1 + 2 + \dots + 6)\}/13$) for hour, considering 13 hours of data collection per day. For example, if the correct answer was Friday for a day question and the participant responded as Monday, the shortest distance to the correct answer is 1 as data was not collected on the weekends. Since the DEC for day is 1.2 the error score is .83 ($= 1/1.2$). The error score for the day scale was the largest ($M = .83$, $SD = .04$) followed by the hour ($M = .79$, $SD = .05$) and week ($M = .79$, $SD = .04$) error score, but the differences were only numerical ($ps > .05$).

Confidence ratings showed a similar pattern to the error scores, where confidence for the

day scale ($M = 1.56$, $SD = .18$) was lower than the hour ($M = 1.82$, $SD = .17$, $p = .027$) and week scale ($M = 1.83$, $SD = .21$, $p < .001$). The relationships between accuracy and response confidence at each time scale were also examined by calculating point bi-serial correlation coefficients (r_{pb} ; see Figure 5). r_{pb} for the week (.18), day (.36), and hour scales (.28) all showed significant correlations ($ps < .001$) replicating previous studies that show positive correlations between confidence and accuracy performance (e.g., Roediger & DeSoto, 2014).

Error scores and confidence ratings show a similar pattern, where performance in the week and hour scales were better than in the day scale. The results support scale effects since a finer scale (i.e., hour) showed better performance than a coarser scale (i.e., day). However, as discussed previously, the results do not provide evidence for the independence of time scales.

To formally evaluate independence between different time scales, we used pointwise mutual information (PMI) as in Equation 1:

$$PMI(A; B) = \log_2\left(\frac{P(A, B)}{P(A) \cdot P(B)}\right) \quad (1)$$

where, $P(A, B)$ is the probability of correctly recalling both time scale A and B (e.g., week and day) of an event whereas $P(A)$ and $P(B)$ are the probabilities of correctly retrieving time scale A (e.g., week) and B (e.g., day) respectively. PMI of zero indicates that the two events are independent, whereas a value above zero indicates that the events are dependent.

Table 2 shows PMIs calculated for different time scale pairs with p -values from a one-sample t -test against zero. Results showed that all pairs were statistically different from zero. Although previous studies (e.g., Friedman & Wilkins, 1985) have posited that patterns in their data supported independence of time scales, utilizing a formal measure (i.e., PMI), the current

results indicate that there are dependencies between the time scales.

Results from the behavioral data support the idea that each time scale can be retrieved using its own retrieval cue (*i.e.*, scale effects) but, at the same time, there are dependencies among the time scales. Thus, the time scales are not linked as the strength hypothesis assumes, but dependency still exists to a certain degree. One possible explanation for time scales being dependent is that cues for different time scales are correlated due to repeating schedules in everyday life. Considering that most of the participants were university students who have a fixed schedule, many of the events they experience may repeat, and different time scales in these events would be correlated, for example, attending class on a specific day and time.

A way to examine repeating events is by using recurrence plots (see Marwan, Carmen Romano, Thiel, & Kurths, 2007, for a review). Recurrence plots are heat-maps of a distance matrix that allow one to examine the repeating patterns visually, and has been used in previous studies to identify repeating visual context (*e.g.*, Sreekumar et al., 2014). To create recurrence plots, we followed the method of Sreekumar et al. (2014) by first converting images from RGB to HSV space, where the values were quantized into 192 colors (*i.e.*, 12 hue, 4 saturation, and 4 lightness levels) for computational efficiency. Color correlograms were then calculated for each image (Huang, Kumar, Mitra, Zhu, & Zabih, 1997). A color correlogram is a three dimensional table that describes the probability of finding one color (C_i) given another color (C_j) at a certain pixel distance (k) of an image. A color correlogram is one way to define the representation of an image, which has been successfully used previously (see Sreekumar et al., 2014, for comparing different image representations). For the current study, the summed color correlogram of $k = \{1, 3, 5, 7\}$ was used. Then the distance matrix was constructed using Euclidean distance of the color

correlogram of each image.

Figure 6 shows the recurrence plot for subject 9. Each point in the plot represents the distance between two images' color correlogram ordered from the first Monday (Mon1) to the last Friday (Fri2), where the distance is color coded from black to white. For example, the diagonal from the bottom-left to the upper-right represents the distance between the identical images, and therefore shows all zero distances colored in black. In the plot, darker colors, which indicate similar visual context, can be identified around the diagonal of the first Tuesday and Wednesday. These dark colors show that a context with similar visual representations is continuing for a period of time. For example, a class could be continuing for a period of time, where the visual representation of that period would be similar. Importantly, the dark patches could be identified on the off-diagonal as well. When looking at the column for the first Tuesday (Tue1), dark patches notably reappear at the intersection of Mon1, Wed1, Fri1, Mon2, Tue2, and Fri2. The recurring dark patches imply that a visual context similar to that of the first Tuesday is repeating on other days (*e.g.*, the participant regularly attending class in a classroom). The recurrence plot provides evidence of events being repeated for subject 9 (see Appendix for similar patterns in all of the subjects' recurrence plots), supporting the argument of different time-scale cues becoming more associated through repeating events.

General Discussion

The current study examined whether memories of different time scales are independently represented. To overcome the shortcomings of the previous studies, we used experience sampling techniques to obtain a better representation of everyday life, and utilized PMI as a formal measure for independence. We find evidence that although each time scale is directly

accessible (*i.e.*, existence of the scale effects), different time scales are not independently represented as has been previously argued (*i.e.*, PMI greater than zero for all time scale pairs).

Most importantly, evidence for dependencies among different time scales is an interesting and novel finding. Previous arguments that time scales are independent (*e.g.*, Friedman, 1993; Neath & Surprenant, 2002) have been based on studies that show scale effects (*e.g.*, Friedman & Wilkins, 1985; Friedman, 1987; Huttenlocher et al., 1992; Larsen & Thompson, 1995).

However, the existence of the scale effects serves no more than a counter-example to falsify a pure strength hypothesis, which assumes that all time scales are perfectly dependent to one another (see Figure 1A and 2). The key contribution of the current study is instead using a formal (and direct) measure of dependency (*i.e.*, PMI) to evaluate dependencies among time scales.

The current study also shows evidence for scale effects as the error score and confidence rating for the hour scale (*i.e.*, finer scale) showed better performance than that of the day scale (*i.e.*, coarser scale). The scale effects imply that the dependency among time scales are not rooted in the strength hypothesis. The necessity of an additional or alternative mechanism to the strength-based mechanism is also shown in the formal version of the strength hypothesis that we introduced in the introduction (see Figure 2). Figure 2B shows probability correct for each time scale as we change the noise level in the model (*i.e.*, SD; standard deviation of the noise distribution), and the dotted lines presents data from the current study. The model predicts almost perfect accuracy for week (green line) when the noise is small, and some degree of noise should be assumed to predict the accuracy level of the current study (*i.e.*, .61). However, as we increase the noise level, accuracy for the hour scale (orange line) rapidly declines below the accuracy of the current study (*i.e.*, .22). A similar pattern is shown for the accuracy of the day

scale. The discrepancy between the model prediction and the actual data implies that the strength-based process is not enough to explain how different time scales are used and represented, and there are additional (or alternative) processes that aid the retrieval of a finer scale such as the hour or day scale.

As suggested by Friedman and Wilkins (1985), a reconstructive hypothesis, or more specifically a location-based process (Friedman, 1993), could predict better retrieval accuracy for the finer scales. The location-based process assumes that there are cues associated with time scale information that enables one to “reconstruct” the time information (*e.g.*, estimating the time of a local earthquake as 11:50am based on the fact that the earthquake happened right before lunch time; Friedman, 1987). Therefore, the time scale that has a stronger cue associated to it will show better retrieval. However, an important point that is less discussed in these theories is that time scale dependency could be predicted when the cues are dependent. The recurrence plot from the current study shown in Figure 6 highly supports this idea, where a fixed schedule provides opportunities for two time scales cues to be repetitively encoded together (*e.g.*, I have a Cognitive Psychology class on Mondays 3pm). As the cues become more associated, retrieval of the time scales that are linked to these cues become more dependent. For example, the fact that the highest PMI is between the day and hour scale (*i.e.*, .36) would reflect the fact that the participants, who were mostly university students, have more dependent cues for the hour and day scales through their academic timetables.

The notion that different time scales and cues are interdependent well aligns with theories of autobiographical memory (*e.g.*, Barsalou, 1988; Conway & Pleydell-Pearce, 2000; Kolodner, 1983), which propose that when we experience an event, we comprehend the event by retrieving

both generic knowledge relevant to that event and specific, related prior events. For example, Barsalou (1988) described an autobiographical free recall experiment where participants were asked to describe the events they experienced in the prior summer in the order that they came to mind. Participants primarily described generic event types (*e.g.* several occasions of playing tennis) followed by specific events (*e.g.* a short event such as a picnic) and extended events (*e.g.* a job that extends across days, interrupted by evenings spent with family). Similar results were obtained in another experiment where they explicitly intervened to instruct participants to only describe specific events. Barsalou concluded that retrieving extended and generic event types was an important part of accessing information about a target period of one's life and constructed a theory of autobiographical memory which was motivated by three findings: (1) the importance of chronologically organized extended events in free-recall verbal protocols, (2) other types of organization, such as by activity, people, and location, and (3) the prevalence of summarized (over multiple occurrences) event types in free-recall protocols. Of these, Barsalou identifies extended-event hierarchical timelines as central to providing people with a way of *telling time in autobiographical memory*. Barsalou's theory (also see Conway and Pleydell-Pearce, 2000 for a similar view), along with the use of the location-based process, will also produce scale dependence. For example, a student-participant during a semester would not only have specific memories about each class she took, but also have built a hierarchical experience structure about their class schedule (*e.g.*, Cognitive psychology class on Mondays at 3pm). If the the participant was asked to estimate the time of an event that was related to her Cognitive psychology class (*e.g.*, meeting a friend right before the class), this information about the class would be used as a cue to retrieve the hour information (*e.g.*, sometime before 3pm since it was before the class).

Moreover, since the cues are interlinked in the hierarchical structure, other time-scales will be more likely to be retrieved (e.g., it would be Monday since it was before the Cognitive psychology class I have on Mondays, etc.).

Another contribution of the current study is in the use of experience sampling methods to provide a way to capture better samples of our daily life. Regarding the current study, it would not have been possible for previous methods (e.g., using news events) to capture the repetitive nature of our daily life, and test each event that was captured (*i.e.*, showing images as a query at test). As discussed earlier, it is highly possible that dependency among time scales stems from the repetitive events that participants encountered. This is not to say that samples from previous studies (e.g., Friedman & Wilkins, 1985) are invalid. Since previous studies did not formally measure dependency, it is possible that events that do not repeat and have a longer retention interval (e.g., asking when John F. Kennedy's assassination was) may have dependency among time scales, and it would be a matter of future investigation. However, what experience sampling, which automatically logs one's daily events, provides is a more uniform sample that covers both repetitive and non-repetitive events, and is a more ecologically valid sample of the memories of everyday life.

References

- Barsalou, L. W. (1988). The content and organization of autobiographical memories. In *Remembering reconsidered: Ecological and traditional approaches to the study of memory*. (pp. 193–243). New York, NY, US: Cambridge University Press.
- Chow, T. E., & Rissman, J. (2017). Neurocognitive mechanisms of real-world autobiographical memory retrieval: insights from studies using wearable camera technology. *Annals of the New York Academy of Sciences*, 1396 (1), 202–221.
- Conway, M. A., & Pleydell-Pearce, C. W. (2000). The construction of autobiographical memories in the self-memory system. *Psychological Review*, 107 (2), 261–288.
- Dennis, S. J., Yim, H., Sreekumar, V., Evans, N. J., Garrett, P., & Sederberg, P. (2017). A hierarchical Bayesian model of 'memory for when' based on experience sampling data. In G. Bunzelmann, A. Howes, T. Tenbrink, E. Davelaar (Eds.) *Proceedings of the 39th Annual Conference of the Cognitive Science Society*, (pp. 295-300). Austin, TX: Cognitive Science Society.
- Dennis, S., Yim, H., Sreekumar, V., Garrett, P., & Stone, B. (2018). A system for collecting and analyzing experience sampling data. <https://doi.org/10.31234/osf.io/tvx7g>
- Efron, B., & Tibshirani, R. (1997). *An Introduction to the Bootstrap*. New York: Chapman and Hall.
- Friedman, W. J. (1987). A follow-up to “Scale Effects in Memory for the Time of Events”:

The earthquake study. *Memory & Cognition*, 15 (6), 518–520.

Friedman, W. J. (1993). *Distance and location processes in memory for the times of past events* (Vol. 35). Elsevier Masson SAS.

Friedman, W. J., & Wilkins, A. J. (1985). Scale effects in memory for the time of events. *Memory & Cognition*, 13 (2), 168–175.

Hinrichs, J. V. (1970). A two-process memory-strength theory for judgment of recency. *Psychological Review*, 77 (3), 223–233.

Huang, J., Kumar, S. R., Mitra, M., Zhu, W., & Zabih, R. (1997). Image indexing using color correlograms. *IEEE Computer Society Conference on Computer Vision and Pattern Recognition*(February), 762–768.

Huttenlocher, J., Hedges, L. V., & Prohaska, V. (1992). Memory for day of the week: a 5 + 2 day cycle. *Journal of Experimental Psychology. General*, 121 (3), 313–325.

Kolodner, J. L. (1983). Reconstructive Memory: A Computer Model. *Cognitive Science*, 7 (4), 281–328.

Larsen, S. F., & Thompson, C. P. (1995). Reconstructive memory in the dating of personal and public news events. *Memory & Cognition*, 23 (6), 780–790.

Marwan, N., Carmen Romano, M., Thiel, M., & Kurths, J. (2007). Recurrence plots for the analysis of complex systems. *Physics Reports*, 438 (5-6), 237–329.

Neath, I., & Surprenant, A. (2002). *Human Memory: An Introduction to Research, Data, and*

Theory (2nd ed.). Wadsworth Publishing.

Nielson, D. M., Smith, T. A., Sreekumar, V., Dennis, S., & Sederberg, P. (2015). Human hippocampus represents space and time during retrieval of real-world memories. *Proceedings of the National Academy of Sciences of the United States of America*, 112 (35), 11078-11083.

Oliva, A., & Torralba, A. (2001). Modeling the shape of the scene: A holistic representation of the spatial envelope. *International Journal of Computer Vision*, 42 (3), 145–175.

Pech-Pacheco, J. L., Cristobal, G., Chamorro-Martinez, J., & Fernandez-Valdivia, J. (2000). Diatom autofocusing in brightfield microscopy: a comparative study. In *Proceedings 15th international conference on pattern recognition. icpr-2000* (Vol. 3, pp. 314–317 vol.3).

Roediger, H. L., & DeSoto, K. A. (2014). Confidence and memory: Assessing positive and negative correlations. *Memory*, 22 (1), 76–91.

Sreekumar, V. (2015). *Context in the wild: Environment, behavior, and the brain* (Unpublished doctoral dissertation). The Ohio State University.

Sreekumar, V., Dennis, S., Doxas, I., Zhuang, Y., & Belkin, M. (2014). The geometry and dynamics of lifelogs: Discovering the organizational principles of human experience. *PLoS ONE*, 9 (5), 1–8.

Sreekumar, V., Nielson, D. M., Smith, T. A., Dennis, S. J., & Sederberg, P. B. (2018). The experience of vivid autobiographical reminiscence is supported by subjective content

representations in the precuneus. *Scientific Reports*, 8 (1), 14899.

Unforgettable Technologies. (2017). *Unforgettable [Software]*.

Table 1

Accuracy for each time scale with mean accuracy (M), standard deviation of the bootstrapped samples (SD), chance-level for each time scale, and Holm-Bonferroni corrected (HBC) empirical p -value against each chance-level derived from bootstrapping.

	M	SD	chance-level	p -value
P (week)	.61	.022	.50 (= 1/2)	< .001
P (day)	.34	.029	.20 (= 1/5)	< .001
P (hour)	.22	.016	.077 (= 1/13)	< .001

Table 2

Pointwise mutual information (PMI) between different time scales with mean PMI (M), standard deviation of the bootstrapped samples (SD), and Bonferroni-Holm corrected empirical p -value against zero from bootstrapping.

	<i>M</i>	<i>SD</i>	<i>$p - value$</i>
<i>PMI(week; day)</i>	.169	.049	< .001
<i>PMI(week; hour)</i>	.124	.052	.020
<i>PMI(day; hour)</i>	.361	.103	.003

Figure 1. Theories that explain how people retrieve different time scale information of an event. (A) Strength hypothesis, and (B) Reconstructive hypothesis.

Figure 2 . Simulation results from a formal strength model being applied to the current study. (A) an example of the model when the correct time point was 10am, Tuesday, Week1. Probability correct of each time scale could be derived from the area under the curve – P(week) shaded in green, P(day) shaded in yellow, and P(hour) shaded in orange, where the area for the wider range (*e.g.*, green) includes the narrower range (*e.g.*, yellow, orange). (B) accuracy of each time scale as a function of the noise distribution (SD), where accuracy data from the current study is also plotted in dotted lines.

Figure 3. Apparatus used in the study. (A) Participants wore a smartphone around their neck during the data collection phase, (B) the layout of the Unforgettable app which was used for data collection. In order to ensure participant's privacy, participants were able to turn on/off the whole app. (image on the left), or the recording of a specific sensor (image in the center), and were also able to delete events that were already recorded (image on the right).

[Please look at the photo on the left and answer the questions below]

1. In which week was the photo taken?

1st Week

2nd Week

>>> How confident are you in your answer above?

Not at all
Confident

Not very
Confident

A little
Confident

Somewhat
Confident

Very
Confident

2. On which day was the photo taken?

Mon

Tue

Wed

Thu

Fri

>>> How confident are you in your answer above?

Not at all
Confident

Not very
Confident

A little
Confident

Somewhat
Confident

Very
Confident

3. At which time of day was the photo taken? (e.g., selecting AM, 2-3 means between 2:00 ~ 3:00 in the morning)

0-1

1-2

2-3

3-4

4-5

5-6

6-7

7-8

8-9

9-10

10-11

11-12

>>> How confident are you in your answer above?

Not at all
Confident

Not very
Confident

A little
Confident

Somewhat
Confident

Very
Confident

4. Please rate how you felt about the event that was occurring when the photo was taken?

Very Negative

Negative

Neutral

Positive

Very Positive

Submit Answers

Figure 4. An example layout of a test trial that was administered online.

Figure 5. Accuracy by confidence rating for (A) week, (B) day, and (C) hour. Values on the x-axis represent confidence rating scores from ‘Not at all confident’ (1) to ‘Very confident’ (5). Dotted lines represent chance level for each time scale, error bars represent the standard deviation of the bootstrapped samples. Point biserial correlations (r_{bs}) are presented for each time scale, where *** represents Holm-Bonferroni corrected empirical $p < .001$. Error bars represent ± 1 standard deviation of the bootstrapped samples.

Figure 6. Recurrence plot for subject 9 using color correlogram image representation. Each intersection represents the Euclidean distance between the two corresponding images. Blue lines represent the border of each day.

Appendix

Individual recurrence plots.

Figure A1 . Individual recurrence plots. Subject 1 to 10 (subject 9's plot is presented in the main text).

Figure A2 . Individual recurrence plots. Subject 11 to 19.