Running head: Pseudo-haptic sense of resistance

Sense of resistance for a cursor moved by user's keystrokes

Takahiro Kawabe*, Yusuke Ujitoko, Takumi Yokosaka, & Scinob Kuroki

NTT Communication Science Laboratories
Nippon Telegraph and Telephone Corporation

*Corresponding author

3-1, Morinosato Wakamiya, Atsugi, Kanagawa, 243-0198, Japan

Tel: +81-46-240-3592

E-mail: takkawabe@gmail.com

Abstract

Haptic sensation of a material can be modulated by its visual appearance. A technique that utilizes this visual-haptic interaction is called pseudo-haptic feedback. Conventional studies have investigated pseudo-haptic feedback in situations wherein a user manipulated a virtual object using a computer mouse, a force-feedback device, etc. The present study investigated whether and how it was possible to offer pseudo-haptic feedback to a user who manipulated a virtual object using keystrokes. Participants moved a cursor toward a destination by pressing a key. While the cursor was moving, the cursor was temporarily slowed down on a square area of the screen. The participants' task was to report, on a 5-point scale, how much resistance they felt to the cursor's movement. In addition to the basic speed of the cursor, the ratio of the basic speed to the speed within the square area was varied. In Experiment 1, we found that these two factors interacted significantly with each other, but further analysis showed that the cursor speed within the square area was the most important determinant of perceived resistance. In Experiment 2, consistent with the results of the previous experiment, it was found that the cursor movement outside of the square area was not required to generate the sense of resistance. Counterintuitively, in Experiment 3, the sense of resistance was apparent even without user's keystrokes. We discuss how the sense of resistance for a cursor moved by keystrokes can be triggered visually, but interpreted by the brain as a haptic impression.

Keywords: sense of resistance; pseudo-haptic feedback, cursor speed

Introduction

One of the important goals of the brain's perceptual system is to generate coherent perceptual representations of the world on the basis of sensory inputs. Importantly, sensory modalities are not independent of each other (Shimojo & Shams, 2001), so the representation generated by the brain is in general cross-modal (or multimodal). Based on the cross-modal interaction between haptics and vision, it is known that haptic experience is strongly modulated by visual inputs (Lederman & Abbott, 1981; Rock & Victor, 1964; Singer & Day, 1969). More recent studies have shown that haptic experience is dependent on the optimal integration of haptic and visual inputs (Ernst & Banks, 2002; Hillis et al., 2002).

Pseudo-haptic feedback (Lécuyer, 2009) is an information presentation technique that, from an engineering point of view, aims to modulate haptic sensations by changing visual appearance. In the typical situation of pseudo-haptic feedback, users manipulate a virtual object in a visual display by controlling haptic devices. Changing the visual appearance of the visual object often provides illusory haptic sensations to the users manipulating the object. For example, previous studies have shown that pseudo-haptic feedback can modulate the perception of virtual spring compliance (Lécuyer et al., 2000), friction (Lécuyer et al., 2000; Ujitoko et al., 2019a), object edge angle (Ban et al., 2012), mass (Dominjon et al., 2005; Issartel et al., 2015; Yu and Bowman, 2020), weight (Brewster et al., 2019), and texture (Sato et al., 2020; Ujitoko et al., 2019b). A key principle of pseudo-haptic feedback is the spatio-temporal dissociation of vision, haptics, proprioception, and motor control. In particular, the ratio of the amplitude of the hand motion (i.e., Control) to the amplitude of the cursor motion (i.e., Display), the so-called C/D ratio (Dominjon et al., 2005; Lécuyer et al., 2004), plays an important role in pseudo-haptic feedback.

So far, pseudo-haptic feedback has been studied in situations where a user manipulates a virtual object (e.g., a cursor) by operating a computer mouse (Lécuyer, et al., 2004, 2005; Kumar et al., 2017), tablet PCs (Ujitoko et al., 2015; Costes et al., 2019), pen devices (Ujitoko et al., 2019 a, 2019b), virtual hands (Sato et al., 2019), real objects (Brewster et al., 2019), and mixed reality technologies (Ban et al., 2012; Issartel et al., 2015; Kawabe, 2020). The use of these devices involves hand movements that are more or less consistent in direction with the movement of the virtual object. For example, if a user makes a hand movement to the right in the real

world, the virtual object will move to the right on the screen. The magnitude of the movement of the virtual object is controlled based on a predetermined C/D ratio.

On the other hand, it is also possible to move a virtual object without making directional hand movements that coincide with the movement of the virtual object. A typical such device is the game controller. In a video game application, a user employs the direction pad of the game controller to control a virtual object/character. By pressing down on a part of the direction pad, the virtual object/character moves in a two- or three-dimensional virtual world. A key point is that the direction of movement of keystrokes on the direction pad does not coincide with the direction of movement of the virtual object; when a key is pressed down, the virtual object moves in the two-dimensional and/or three-dimensional directions in the display. Another key point is that the distance moved by the virtual character depends on the length of time the user holds down the assigned key, whereas in the typical situation of pseudo-haptic feedback research, the movement distance of the virtual object depends on how much the user moves her/his hand. Thus, the control of the virtual character based on keystrokes depends on different information from that used in the control based on hand movements that have been used in previous pseudo-haptic studies. Because of this, it was unclear whether we could provide pseudo-haptic feedback to a user who controlled the virtual object using keystrokes. A previous study (Argelaguet et al., 2015) employed a change in color of the cursor caused by the user pressing a mouse button as additional visual feedback in judging pseudo-haptic elasticity. However, until now little systematic knowledge has been acquired on the role of keystrokes in pseudo-haptic feedback.

In the present study, we attempted to specify stimulus conditions that would provide a sense of resistance to a user who manipulated a cursor only using keystrokes. In previous studies, pseudo-haptic feedback has been discussed in terms of physical properties such as friction (Lécuyer et al., 2000; Ujitoko et al., 2019a), mass (Dominjon et al., 2005; Issartel et al., 2015; Yu and Bowman, 2020), and viscosity (Costes et al., 2019). In the present study, experimental participants manipulated the cursor by keystrokes, and the stimuli observed by the participants consisted of simple geometric patterns such as squares and circles. Therefore, there was no sufficient *a priori* reason to attribute pseudo-haptic impressions, which would be obtained in the experimental situation of the present study, to a certain type of the physical properties. We consider the sense of resistance as a higher-order component of the pseudo-

haptic impressions that have been discussed in terms of the physical properties as described above. By investigating the sense of resistance, we surmise that it is not necessary to assume any relationship between pseudo-haptic impressions and physical properties. Hence, we decided to ask the participants to report their sense of resistance.

In the experiments reported in this study, the movement of the cursor, initiated by keystrokes, was slowed down when the cursor entered a square area in the center of the display. For the cursor speed, two factors were varied: the basic speed and the speed ratio. The basic speed was the cursor speed when outside the square area. The speed ratio was the ratio of the cursor speed inside the square area to the cursor speed outside the square area. In Experiment 1, we examined whether and how the two factors of cursor speed affected the sense of resistance. In Experiment 2, we tested whether the pattern of speed change along the cursor path was important in determining the sense of resistance. In Experiment 3, we examined whether continuous operation of a key is a necessary factor for resistance. Based on the results obtained, it is concluded that the sense of resistance for the cursor moved by keystrokes originates from visual effects, and at the same time, the cross-modal transfer (Biocca et al., 2001) causes haptic sensations related to the sense of resistance.

Experiment 1

Purpose

The purpose of the experiment was to examine whether the participants could feel resistance to the cursor moving with their keystrokes. In the experiment, the participants controlled the movement of the cursor by pressing and holding down a key on the keyboard. The cursor was operated at 3 basic speeds (actually 2, 4 and 6 pixels/ display frame of the computer monitor). When the cursor passed through the central square area, the speed was reduced with the three levels of speed ratio. The effect of speed ratio and basic speed on the degree of resistance was tested.

Method

Participants 202 people (101 females) participated in this experiment. Their mean age was 39.73 (SD11.33). A Japanese crowdsourcing research company recruited them online and paid for their participation. They were unaware of the

specific purpose of the experiment. Ethical approval for this study was obtained from the ethics committee at Nippon Telegraph and Telephone Corporation (Approval number: R02-009 by NTT Communication Science Laboratories Ethics Committee). The experiments were conducted according to principles that have their origin in the Helsinki Declaration. Written informed consent was obtained from all observers in this study.

Apparatus The experiment for this study was carried out on a personal computer (PC) provided by the participant. Since the experimental script runs only on a PC, a smartphone or a tablet PC could not be used. The viewing distance and the screen size were not controlled because their effect was not evident in the preliminary observation as long as the user used the PC under normal use conditions.

Figure 1 (a) Snapshot of the stimulus with the description of the components. Arrows and text are used to describe the stimulus components and are not shown in the actual experiment. (b) Schematic graph showing the change in cursor speed over

the cursor path. As shown in the inset, the speed ratio is defined as v_2/v_1 . Vertical dashed lines show the correspondence between the spatial positions in (a) and (b).

Stimuli As shown in Figure 1, the stimuli consisted of a square cursor (16 x 16 pixels, with RGB values [192,192,192]), a square area (120 x 120 pixels, with RGB values [64, 64, 0]), a target circle (16 pixels in diameter with RGB values of the contour [32, 32, 32]), and a uniform background with RGB values [128,128,128]. The initial locations of the cursor (and thus the target), and hence the direction of travel of the cursor from left to right or right to left, were randomly determined from trial to trial. When the cursor appeared 200 pixels to the left of the left edge of the square area, the target appeared 200 pixels to the right of the right edge of the square area. On the other hand, when the cursor appeared 200 pixels to the right of the right edge of the square area, the target appeared 200 pixels to the left of the left edge of the square area. The cursor moved toward the target only when the participant held down an assigned key (i.e., the M key on the computer keyboard). Because the square area was centered in the display, the cursor went across the square area to reach the target. Outside the square area, the cursor moved at a speed of 2, 4, or 6 pixels per frame. This speed is called "basic speed". Within the square area, the cursor moved at the basic speeds of 0.25x, 0.5x, and 1x the basic speed. This modulation of velocity in the square area is called the "speed ratio".

Procedure At the beginning of the experiment, the participants were presented with written instructions that described the situation and tasks of the experiment. After reading this, the participant pressed the space key on the computer keyboard to start the experiment. The participant's task was to hold down the M key and so allow the cursor to move toward the target. The stimulus images disappeared after the cursor reached the target. The participants then assessed how much resistance they felt while the cursor was moving over the square area. They reported the evaluation on a 5-point scale by pressing the assigned keys, wherein 5 represented the highest resistance. After reporting their impression, the next trial began. Each experimental condition was repeated 5 times. Thus, each participant performed 45 trials (3 basic speed conditions × 3 speed ratios × 5 iterations) in a pseudo-random order.

Results

For each condition, rating scores were averaged for each participant. Mean rating scores across the participants are shown in Figure 2(a). By using ‘vegan’ (Oksanen et al., 2020) and ‘EcolUtils’ (Salazar, 2020) packages of R (R Core Team, 2020), a two-way permutation analysis of variance (Anderson, 2001; Anderson & Walsh, 2013) was conducted with the basic speed and speed ratios as within-subject factors. The main effect of the basic speed was significant [$F = 198.58$, $p < .001$, $r^2 = 0.08$]. The main effect of the speed ratio was also significant [$F = 1113.16$, $p < .001$, $r^2 = 0.49$]. The interaction between them was significant [$F = 19.45$, $p < .001$, $r^2 = 0.017$]. All post-hoc t-tests on the basis of the significant interaction reached significance ($p < .05$ with the Bonferroni correction).

Figure 2. Experiment 1 results. (a) For each of the basic speeds, rating scores for the sense of resistance are plotted as a function of the speed ratio. (b) The rating scores are plotted as a function of the cursor speed on the square area.

Although the interaction between the basic speed and speed ratio was clear, the rating scores might simply depend on the cursor speed on the square area. Figure 2(b) plots the rating score as a function of the cursor speed on the square area. We can see the rating score clearly depends on the cursor speed. By using data from all participants,

we performed a linear regression analysis and found the regression to be significant [*Adjusted* $r^2 = 0.47$, $F(1, 1825) = 1662$, $p < .001$]. Furthermore, the cursor speed on the square area significantly contributed to the regression [$t = -40.77$, $p < .001$].

As a result, it was found that the cursor speed in the square area was critical to generating the sense of resistance. As we varied the basic speed and the speed ratio as experimental factors, the cursor speed within the square area also varied with the changes. As shown in Figure 2(b), and by the regression analysis, the rating scores can be well described by a single parameter, the cursor speed when in the square area. In a sense, the results are consistent with the previous results (Dominjon et al., 2005; Lécuyer, et al., 2004) showing that the C/D ratio regulates the pseudo-haptic feedback. In the current experiment, since the cursor movement was controlled by pressing and holding down a key, the speed of hand movement was kept almost constant. Therefore, for the C/D ratio, C was a constant, and thus, the C/D ratio in this experiment depended only on D, i.e., the cursor speed.

It was still unclear whether the speed ratio had any effect on the sense of resistance because the modulation of the speed ratio was not experimentally dissociated from the variation of the cursor speed in the square. In the next experiment, we attempted to clarify this issue.

Experiment 2

Purpose

The purpose of the experiment was to check whether a sense of resistance could be caused even when the cursor did not move outside the square area and thus no speed ratio could be obtained. The results of the previous experiment showed that the cursor speed within the square area was critical to regulating the sense of resistance, indicating that the movement path outside the square area might possibly play a minor role in determining the sense of resistance. In the current experiment, we completely or partially removed the path outside the square area to see the effect of the path on the sense of resistance.

Method

Participants 203 people (101 females), who had not participated in Experiment 1, participated in this experiment. Their mean age was 40.25 (SD11.25).

Stimuli The stimuli were identical to those used in Experiment 1 except for the following. We tested four conditions (in other words, there are three new conditions in addition to the previous one) on the movement path of the cursor. As in the Experiment 1, the appearance locations of the cursor (and thus the target) were randomly determined from trial to trial. In the 'ABC' condition [Figure 3(a)], as in Experiment 1, when the cursor appeared 200 pixels to the right of the right edge of the square area, it moved through the square area to the target presented 200 pixels to the left of the left of the square area. When the cursor appeared 200 pixels to the left of the left edge of the square area, it moved through the square area to the target presented 200 pixels to the right of the right of the square area. In the 'AB' condition [Figure 3(b)], when the cursor appeared 200 pixels to the right of the right edge of the square area, it moved through the square area to the target presented at the left edge of the square area. When the cursor appeared 200 pixels to the left of the left edge of the square area, it moved through the square area to the target at the right edge of the square area. In the 'BC' condition [Figure 3(c)], when the cursor appeared at the right edge of the square area, it moved through the square area to the target presented 200 pixels to the left of the left edge of the square area. When the cursor appeared at the left edge of the square area, it moved through the square area to the target presented 200 pixels to the right of the right edge of the square area. In the 'B' condition [Figure 3(d)], when the cursor appeared at the right edge of the square area, it moved through the square area to the target presented at the left of the square area. When the cursor appeared at the left edge of the square area, it moved through the square area to the target presented at the right edge of the square area. The basic speed was kept constant at 4 pixels/frame for all trials. In each trial, the speed ratio was randomly selected from among three candidates of 0.25x, 0.5x, and 1x. Since we used only one level of the basic speed, the cursor speed in the square area was 1, 2, and 4 pixels/frame.

Figure 3. Schematic explanations of the movement path of the square cursor in the Experiment 2 stimuli. The labels 'A', 'B', and 'C' as well as the lines and arrows are used to describe the path patterns and were not presented in the actual experiment.

Procedure The procedure was identical to that used in Experiment 1 except for the following. Each participant performed 60 trials (4 movement paths $\times$ 3 speed ratios $\times$ 5 iterations) in a pseudo-random order.

Results and Discussion

For each condition, rating scores were averaged for each participant. Mean rating scores across the participants are shown in Figure 4. By using individual mean rating scores, a two-way permutation analysis of variance was conducted with the movement trajectories and speed ratios as within-subject factors. The main effect of the movement trajectories was significant [$F = 5.28$, $p = .002$, $r^2 = 0.003$]. However, the multiple comparison test with the Bonferroni correction did not show any significant difference between any two of the movement trajectories ($p > .05$). The main effect of the speed ratio was significant [$F = 1184.91$, $p < .001$, $r^2 = 0.49$]. The multiple comparison test showed that there were significant differences between any two of the speed ratios ($p = .003$). Interaction between the two factors was not significant [$F = 1.55$, $p = .13$].

The results indicate that the presence/absence of motion paths outside the square area played a minor role in generating the sense of resistance. Because the effect of the speed ratios was significant, the sense of resistance is likely determined on the basis of the cursor speed in the square area, which is consistent with

Experiment 1. Thus, the effect of the speed ratio on the magnitude of the sense of resistance can be attributed to the cursor speed in the square area.

Figure 4. Experiment 2 results. For each of the movement paths, the rating scores for the sense of resistance are plotted as a function of the speed ratio.

Experiment 3

Purpose

The purpose of this experiment was to explore whether the participant's keystrokes played an essential role in generating the sense of resistance. We tested the following three conditions: In a 'hold-down' condition, as in Experiment 1, the participants kept holding down a key to control the cursor movement. In an 'automatic' condition, the participants observed the cursor movement without pressing a key. In a 'release' condition, the participants pressed and then released a key to start the cursor movement. If the participant's action (i.e., pressing a key) was necessary for generating the sense of resistance, the rating scores for the automatic condition would be lower than those for the other conditions. Moreover, if generating the sense of resistance required the participants' continued involvement by their action, the rating scores for the hold-down condition would be greater than that for the release condition.

Method

Participants 203 people (101 females), who had not participated in Experiments 1 and 2, participated in this experiment. Their mean age was 40.11 (SD10.91).

Stimuli The stimuli were identical to those used in Experiment 1 except for the following. We tested three starting conditions (in other words, there are two new conditions in addition to the previous one.) on how the cursor started to move. First, in the "Hold-down" condition, as in Experiment 1, the square cursor moved toward the target only when the participant kept holding down the M key. Second, in the "Automatic" condition, the participants watched the cursor that automatically moved toward the target. Specifically, in the first trial, the cursor moved 2 seconds after the participant started the session by pressing the spacebar on the keyboard. In the second and subsequent trials, the cursor began to move 2 seconds after the participant reported a judgment about the sense of resistance for a previous trial. Third, in the "Release" condition, the cursor moved immediately after the finger was released from the M key. The basic velocity was kept constant at 4 pixels/frame. As in previous experiments, three levels of speed ratio (0.25x, 0.5x, and 1x) were used.

Procedure In each trial, an instruction for starting the cursor movement was presented above the stimuli. In the "Hold-down" condition, the statement "Hold down the M key and watch the cursor move." was presented. In the "Automatic" condition, the statement "Watch the cursor without pressing any keys." was shown. In the Release condition, the statement "Release the M key to move the cursor and observe cursor movement" was presented. Following the instructions, the participants moved and/or observed the cursor. Other aspects of the task were the same as those used in Experiment 1, with the following exceptions. Each observer performed 45 trials [3 starting conditions (Hold-down, Automatic, and Release) x 3 speed ratios x 5 iterations] in a pseudo-random order.

Results and Discussion

For each condition, rating scores were averaged for each participant. Mean rating scores across the participants are shown in Figure 5. By using individual mean rating scores, a two-way permutation analysis of variance was conducted with the starting conditions and speed ratios as within-subject factors. The main effect of the starting

conditions was not significant [$F = 1.52$, $p = .205$, $r^2 = 0.0009$]. The main effect of the speed ratio was significant [$F = 770.05$, $p < .001$, $r^2 = 0.45$]. The multiple comparison test showed that there were significant differences between any combination of the speed ratios ($p = 0.003$). The interaction between them was not significant [$F = 0.16$, $p = .977$, $r^2 = 0.0002$].

The results that the main effect of the starting condition was not significant indicate that the participants' action is not a necessary condition for the generation of the sense of resistance for a cursor moved by user's keystrokes, at least under the conditions we investigated. The sense of resistance is likely a visual phenomenon and the visually-caused sensation is interpreted as the sensation for a moving object under key control.

Figure 5. Experiment 3 results. For each starting condition, rating scores for the sense of resistance are plotted as a function of the speed ratio.

General Discussion

The findings of this study can be summarized as follows. When the cursor, controlled by the participant's keystrokes, slowed down, the participant could sense resistance. The cursor speed itself, rather than the speed ratio on the cursor path, was an important indication of resistance. The participant's keystrokes were not a necessary factor in generating a sense of resistance.

The effect of cursor speed had a critical influence on the sense of resistance. As shown in Figure 2(b), the rating scores of the sense of resistance within the square area decreased linearly as a function of the cursor speed. On the other hand, it remains an open question whether the linear relationship between the sense of resistance and the cursor speed is maintained when the range of the cursor speed is extended. For example, if there are extreme cursor speeds in the stimulus set, the linear relationship is expected to be easily disturbed. Therefore, when designing the sense of resistance in an actual GUI, engineers need to pay attention to the range of cursor speed to provide the desired level of the sense of resistance to the cursor.

It should be noted that our experimental setup does not guarantee that all participants experienced comparable cursor speeds. We controlled the cursor speed in the unit of pixels/frame (i.e., how far the cursor moved in pixels between two consecutive frames). Thus, the actual speed (e.g., in units of cm/sec) varied depending on the spatial and temporal resolutions of the display the participants used for their experiments. In addition, since we controlled neither the size of the display nor the observation distance, the retinal speed (i.e., in deg/sec) was likely to have varied among participants. Despite the potential diversity of displays used in the experiment, the effect of cursor speed on resistance was robust. This suggests that each participant may have judged the resistance based on the relative cursor speed in a given stimulus set. Future research is needed to further clarify possible interactions between absolute and relative cursor speeds, controlling the spatio-temporal resolution of the display, display size, and observation distance.

No effect of participant's action (i.e., keystrokes) was observed. In other words, whether the participants manually controlled the cursor or not had no effect on the magnitude of the sense of resistance. As discussed in Experiment 1, since action involving key control is almost constant, C (i.e., the hand speed) will also be constant when calculating the C/D ratio. Ultimately, the C/D ratio depends on D (i.e., the cursor

speed). We speculate that the reason why we did not observe the effect of key control action on the sense of resistance was simply that the magnitude of motor action and/or haptic stimulation involving keystrokes was smaller than other types of motor action that were tested in the previous studies on pseudo-haptic feedback. The relatively smaller magnitude of motor action compared with visual movements perhaps reduced the contribution of motor action to the cross-modal integration causing the sense of resistance. Future studies should examine whether the effect of motor action on the sense of resistance is observed when the cursor is moved by other motor actions, such as mouse movements, rather than key presses.

Although the difference in motor action did not contribute to the variation in the amount of the sense of resistance, this does not necessarily mean that the sense of resistance observed in this study is a purely visual representation; it is possible that haptic and/or motor components may also be included in the representation of the sense of resistance. When the authors performed the task in a preliminary experiment, they felt a non-visual (or haptic) sense of resistance when manually operating the cursor. This informal experience is consistent with the interpretation based on cross-modal transfer (Biocca et al., 2001). In Biocca et al. (2001), the participants were asked to manipulate objects in the virtual world without receiving force or haptic feedback. Interestingly, the participants reported that they experienced physical force even when neither force nor haptic feedback was given. The authors argued that the illusory haptic sensation was due to cross-modal transfer, or synesthesia (Baron-Cohen, 1996). As is well known, each sensory modality in the brain is not independent of the others (Shimojo & Shams, 2001). The modalities interact with each other to generate cross-modal representations. From this perspective, it is reasonable to assume that visual resistance is transferred to haptic and/or sensorimotor sensations, which are used to generate internally a cross-modal model of the world. Thus, it may be possible to clarify whether or not the sense of resistance forms a cross-modal representation, for example, by examining the brain regions involved in this phenomenon.

One previous study (Watanabe, 2013) reported that pseudo-collision impression was induced by the sudden slowdown of a moving object, which occurred when the object and a mouse cursor were spatially coincident with each other. At first glance, the results of the previous study and the present study appear to be inconsistent. In the present study, the cursor speed after slowing down was important

for the magnitude of the sense of resistance, whereas, in Watanabe (2013), the object speed after slowing down was not the only factor determining the pseudo-collision impression. We suggest, however, that the difference in the pattern of results may reflect the differences in procedures and stimuli between the previous study and the present study. In the previous study, the participants were asked to report the magnitude of pseudo-collision impression. In the typical case of object collision, the speed of the moving object is expected to slow down after the collision, so it is likely that the relative movement speed was used as a cue to determining the pseudo-collision impression. In the present study, on the other hand, we asked the participants to report the sense of resistance when the cursor passed over the square area. The task of the current study was possibly made feasible by focusing on the cursor speed within the square area only. The difference in motion patterns on which the participants relied to perform the task is possibly the cause of the difference between Watanabe's (2013) and present studies. Although in Watanabe (2013) the pseudo-collision impression was not induced when no speed reduction was applied to the moving object, the sense of resistance was generated in the present study even when the cursor speed did not change along the cursor path as long as it was sufficiently low, as observed in the lowest basic speed condition with the speed ratio of 1. Thus, we suggest that the pseudo-collision impression is likely a perceptual phenomenon different from the sense of resistance.

To sum up, is the sense of resistance shown in this study different from the pseudo-haptic sensations that have been repeatedly shown in previous studies? We believe that they are essentially the same thing. However, the contribution of this study is that we showed that keystrokes can be proposed as an implementation condition for generating pseudo-haptic sensation. In addition to the aforementioned direction pad, there are other devices that control virtual/real objects by keystrokes, such as devices for controlling drones. The results of the present study suggest the possibility of providing pseudo-haptic sensation to such control devices using keystrokes.

References

Anderson, M. J. (2001). A new method for non-parametric multivariate analysis of variance. *Austral Ecol* 26, 32–46. doi:10.1111/j.1442-9993.2001.01070.pp.x.

Anderson, M. J., and Walsh, D. C. I. (2013). PERMANOVA, ANOSIM, and the Mantel test in the face of heterogeneous dispersions: What null hypothesis are you testing? *Ecol Monogr* 83, 557–574. doi:10.1890/12-2010.1.

Argelaguet, F., Jáuregui, D. A. G., Marchal, M., and Lécuyer, A. (2013). Elastic images: Perceiving local elasticity of images through a novel pseudo-haptic deformation effect. *Acm Transactions Appl Percept Tap* 10, 17. doi:10.1145/2501599.

Ban, Y., Kajinami, T., Narumi, T., Tanikawa, T., and Hirose, M. (2012). Haptics: Perception, Devices, Mobility, and Communication, International Conference, EuroHaptics 2012, Tampere, Finland, June 13-15, 2012. Proceedings, Part I. *Lect Notes Comput Sc*, 25–36. doi:10.1007/978-3-642-31401-8_3.

Baron-Cohen, S. (1996). Is There a Normal Phase of Synaesthesia in Development? *PSYCHE* 2, 1–7.

Biocca, F., Kim, J., and Choi, Y. (2001). Visual Touch in Virtual Environments: An Exploratory Study of Presence, Multimodal Interfaces, and Cross-Modal Sensory Illusions. *Presence Teleoperators Virtual Environ* 10, 247–265. doi:10.1162/105474601300343595.

Brewster, S., Fitzpatrick, G., Cox, A., Kostakos, V., Samad, M., Gatti, E., et al. (2019). Pseudo-Haptic Weight: Changing the Perceived Weight of Virtual Objects By Manipulating Control-Display Ratio. 1–13. doi:10.1145/3290605.3300550.

Costes, A., Argelaguet, F., Danieau, F., Guillotel, P., and Lécuyer, A. (2019). Touchy : A Visual Approach for Simulating Haptic Effects on Touchscreens. *Frontiers Ict* 6, 1. doi:10.3389/fict.2019.00001.

Dominjon, L., Lécuyer, A., Burkhardt, J.-M., Richard, P., and Richir, S. (2005). Influence of Control/Display Ratio on the Perception of Mass of Manipulated Objects

in Virtual Environments. *Ieee Proc Vr 2005 Virtual Real 2005*, 19–25.
doi:10.1109/vr.2005.1492749.

Ernst, M. O., and Banks, M. S. (2002). Humans integrate visual and haptic information in a statistically optimal fashion. *Nature* 415, 429–433.
doi:10.1038/415429a.

Hillis, J. M., Ernst, M. O., Banks, M. S., and Landy, M. S. (2002). Combining Sensory Information: Mandatory Fusion Within, but Not Between, Senses. *Science* 298, 1627–1630. doi:10.1126/science.1075396.

Issartel, P., Guéniat, F., Coquillart, S., and Ammi, M. (2015). Perceiving Mass in Mixed Reality through Pseudo-Haptic Rendering of Newton's Third Law. *2015 Ieee Virtual Real Vr*, 41–46. doi:10.1109/vr.2015.7223322.

Kawabe, T. (2019). Mid-Air Action Contributes to Pseudo-Haptic Stiffness Effects. *Ieee T Haptics* 13, 18–24. doi:10.1109/toh.2019.2961883.

Kumar, A., Gourishetti, R., and Manivannan, M. (2017). Mechanics of Pseudo-Haptics with Computer Mouse. *2017 Ieee Int Symposium Haptic Audio Vis Environ Games*, 1–6. doi:10.1109/have.2017.8240358.

Lécuyer, A. (2009). Simulating Haptic Feedback Using Vision: A Survey of Research and Applications of Pseudo-Haptic Feedback. *Presence Teleoperators Virtual Environ* 18, 39–53. doi:10.1162/pres.18.1.39.

Lécuyer, A., Burkhardt, J.-M., and Etienne, L. (2004). Feeling bumps and holes without a haptic interface: the perception of pseudo-haptic textures. 239–246.
doi:10.1145/985692.985723.

Lecuyer, A., Coquillart, S., Kheddar, A., Richard, P., and Coiffet, P. (2000). Pseudo-Haptic Feedback : Can Isometric Input Devices Simulate Force Feedback? *Proc Ieee Virtual Real 2000 Cat 00cb37048*, 83–90. doi:10.1109/vr.2000.840369.

Lederman, S. J., and Abbott, S. G. (1981). Texture perception: studies of intersensory organization using a discrepancy paradigm, and visual versus tactual psychophysics. *J. Exp. Psychol. Hum. Percept. Perform.* 7, 902–915. doi: 10.1037//0096-1523.7.4.902

Oksanen, J., Blanchet, F. G., Friendly, M., Kindt, R., Legendre, P., McGlinn, D., Minchin, P. R., O'Hara, R. B., Simpson, G. L., Solymos, P., Stevens, M. H. H., Szoecs, E., and Wagner, H. (2020). vegan: Community Ecology Package. R package version 2.5-7. <https://CRAN.R-project.org/package=vegan>

R Core Team (2020). R: A language and environment for statistical computing. R Foundation for Statistical Computing, Vienna, Austria. URL <https://www.R-project.org/>.

Rock, I., and Victor, J. (1964). Vision and Touch: An Experimentally Created Conflict between the Two Senses. *Science* 143, 594–596. doi:10.1126/science.143.3606.594.

Salazar, G. (2020). EcolUtils: Utilities for community ecology analysis. R package version 0.1. <https://github.com/GuillemSalazar/EcolUtils>

Sato, Y., Hiraki, T., Tanabe, N., Matsukura, H., Iwai, D., and Sato, K. (2020). Modifying Texture Perception With Pseudo-Haptic Feedback for a Projected Virtual Hand Interface. *Ieee Access* 8, 120473–120488. doi:10.1109/access.2020.3006440.

Shimojo, S., and Shams, L. (2001). Sensory modalities are not separate modalities: plasticity and interactions. *Curr Opin Neurobiol* 11, 505–509. doi:10.1016/s0959-4388(00)00241-5.

Singer, G., and Day, R. H. (1969). Visual capture of haptically judged depth. *Percept Psychophys* 5, 315–316. doi:10.3758/bf03209572.

Ujitoko, Y., Ban, Y., and Hirota, K. (2019a). Presenting Static Friction Sensation at Stick-slip Transition using Pseudo-haptic Effect. *2019 IEEE World Haptics Conf Whc* 00, 181–186. doi:10.1109/whc.2019.8816100.

Ujitoko, Y., Ban, Y., and Hirota, K. (2019b). Modulating Fine Roughness Perception of Vibrotactile Textured Surface using Pseudo-haptic Effect. *IEEE T Vis Comput Gr* 25, 1981–1990. doi:10.1109/tvcg.2019.2898820.

Ujitoko, Y., Ban, Y., Narumi, T., Tanikawa, T., Hirota, K., and Hirose, M. (2015). Yubi-Toko: Finger Walking in Snowy Scene using Pseudo-haptic Technique on Touchpad. *SIGGRAPH Asia 2015 Emerging Technologies, SA '15*. 1–3. doi:10.1145/2818466.2818491.

Watanabe, J. (2013). [Letter] Pseudo-haptic Sensation Elicited by Background Visual Motion. *Ite Transactions Media Technology Appl* 1, 199–202. doi:10.3169/mta.1.199.

Yu, R., and Bowman, D. A. (2020). Pseudo-Haptic Display of Mass and Mass Distribution During Object Rotation in Virtual Reality. *Ieee T Vis Comput Gr* 26, 2094–2103. doi:10.1109/tvcg.2020.2973056.